

Model:UT-6604

10/100M TCP/IP to 4 Ports RS-232/485/422 Serial Device Server

Datasheet



UTEK TECHNOLOGY (SHENZHEN) CO., LTD.

Add: Floor 8-10, Building 7, Skyworth Innovation Valley, No. 8, Tangtou No.1 Road, Shiyan Street, Shiyan Old Street, Bao 'an District, Shenzhen

Tel: +86-755-81202008

Fax: +86-755-27886083

Http: www.uotek.com

1. Overview

UT-6604 serial device server is a converter that converts asynchronous ports RS-232/422/485 to TCP/IP. It is an independent intelligent device with CPU, embedded OS, and full TCP/IP protocol. The bid-direction transparent transmission between RS-232/422/485 and Ethernet enables RS-232/422/485 serial devices access in Internet immediately.

2. Major Functions & Features

- Supports 10/100M TCP/IP to 4 Ports RS-232/485/422 Serial Device Server


3. Technical Parameters

- Number of serial port: 4
- CPU: 32bit 100MHz
- RAM: 8M
- Baud rate: 50-460800bps
- Check bits: None, Odd, Even, Mark, Space
- Data bits: 5, 6, 7, 8
- Stop bits: 1, 1.5, 2
- Flow control: RTS/CTS, XON/XOFF
- Serial port: RJ-45
- Serial port protection: 400W lightning surge protection
- Signal: RS-232:DCD/DXD/TXD/DTR/GND/DSR/RTS/CTS
- RS-422: TXD+/RXD+/TXD-/RXD-/GND
- RS-485: Data+/Data-
- Network port transmission rate: 10/100M, auto negotiation
- Network port: RJ-45
- Port protection: built-in 2KV electromagnetic isolation
- Protocol: ARP\IP\ICMP\UDP\TCP\PPP\HTTP\TELNET\DNS\DHCP\PAP\CHAP
- Virtual COM: Windows NT/2000/XP
- Operating temperature: -10 ~ 60°C
- Operating humidity: 5% ~ 95%(non-condensing)
- Storage temperature: -20 ~ 85°C
- Storage humidity: 5% ~ 95%(non-condensing)
- Power: DC5V/1A
- Housing: metal
- Dimension: 160x90x30mm

4. Product View (Appearance)



5. Structure Dimensions



6. Ordering Information

Ordering												
Model	Signal/Port		Port qty		Protection		Baudrate	Environment			Power	
	TCP/IP	RS-232/485/422	TCP/IP	RS-232/485/422	TCP/IP	RS-232/485/422		Temperature		Humidity	Port-Powered	External Power
	RJ45	RJ45						-10/60°C	-40/85°C	5-95%		
UT-6604	✓	✓	1	4		400W Surge	50-460.8Kbps	✓		✓		+5VDC
UT-6608	✓	✓	1	8		400W Surge	50-460.8Kbps	✓		✓		+5VDC

Accessories: Power adapter/serial cable/Fixed piece